

# Xprinter®



Direct thermal Printer


## XP-C58H

- High speed, long lifetime, high quality
- Outstanding functions, Strong stability
- Support Linux & Windows system
- Support OPOS driver&Chinese Gb18030
- Avoid order missing
- Compatible with ESC/POS commands



# XP-C58H

## Direct thermal Printer



<b>Model</b>	XP-C58H
<b>Printing method</b>	Direct thermal
<b>Paper width</b>	57.5±0.5mm
<b>Print width</b>	48 mm
<b>Column capacity</b>	384 dots/line(Adjustable by command)
<b>Printing speed</b>	120 mm/s Max.
<b>Interface</b>	USB / Lan / Serial / Parallel
<b>Line spacing</b>	3.75mm (Adjustable by commands)
<b>Fonts Symbology</b>	
<b>Character size</b>	Afont A: 12x24, Font B: 9x17, CHN: 24*24
<b>Characters /Line</b>	Font A: 32 chars Font B: 42 chars CHN: 16 Character Sets
<b>1D Barcode</b>	UPC-A / UPC-E / JAN13(EAN13) / JAN8(EAN8) / CODE39 / ITF / CODABAR / CODE93 / CODE128
<b>Input buffer</b>	32 Kbytes / 64 Kbytes
<b>NV Flash</b>	64 Kbytes
<b>Power</b>	
<b>Power adaptor</b>	AC 110V/220V, 50 ~ 60Hz12VDC, 2.6A
<b>Power source</b>	DC 12V/2.6A
<b>Cash drawer</b>	DC 12V/1A
<b>Physical characteristics</b>	
<b>Weight</b>	0.88kg
<b>Dimensions</b>	180×135×135mm (D×W×H)
<b>Environmental Requirements</b>	
<b>Work environment</b>	Temperature (0 ~ 45°C) humidity(10 ~ 80%)
<b>Storage environment</b>	Temperature(-10 ~ 60°C) humidity(10 ~ 80%)
<b>Reliability</b>	
<b>Printer head life</b>	50Km
<b>Software</b>	
<b>Emulation</b>	ESC/POS
<b>Driver</b>	Windows/JPOS/Linux/Android/Mac
<b>Utility</b>	Windows & Linux test Utility
<b>SDK</b>	iOS, Android, Windows



Scan QR code to checkout Xprinter website for more update information.  
Phone: (+86 756) 3895 852  
Http://www.xprintertech.com  
Email: overseas@xprinter.net

